

The preferred business class telephony solutions is a highly robust and flexible systems, equipped with sophisticated technology and functionality.

ENTERPRISE SERIES

MODEL: Q610

BUSINESS TELEPHONE

Our Key
Advantage

Check out our other
fantastic products:

- > Q608/Q608-Hotel
- > Q628 2 line
- > Q620 LCD 2 line

XENTEL



OUR CUSTOMER SERVICE

Warranty statement: All products
comes with 12 months warranty
with Advance Parts Replacement
program.

The **Q610 Business Telephone** truly complement your enterprise communications strategy and enhances user experience with ergonomic, flexible and cost saving design such as:

- **N'Pad** or number pad allow you to store a number using the phone number pad and retrieve the number after the call.
- **100 Name phonebook** directory with easy to search function based on alphabetical index.
- Powerful yet user friendly functionality such as **100 Caller Log** (50 missed, 25 incoming & 25 outgoing), bring values to your customer service policy.



Overview of Q610 Business Telephone

Enhanced Multi Functional Phone Q610

Call Management

Caller ID & Phone Directory

100 CID Memory

50 missed call

25 Incoming Call

25 Outgoing Call

Caller Name &

Number matching

100 name phonebook

Directory

Missed call

Indicator

Dial from call Log

N'Pad (save Number while talking)

Voicemail light

Indicator(90V)

Last Number Redial

2 way handsfree

Link (flash/Pabx transfer)

Hold with LCD

Indicator)

Mute with Indicator

3 screen interactive keys

Release key

Ringing/Speaker/Handset Volume switch

4 Ringer tone type

Trilingual: English, French and Spanish



3 line LCD Display with Backlight

Message waiting light/ Visual Ringing

Menu Key

Callers/Call Log

Self label/Interactive Key

Navigational Cluster

Release Key

Directory/PhoneBook

Last No Redial

Link/Flash/Transfer

Programmable Keys

Handsfree & Indicator

Hold Key

Mute with Indicator

Volume Control

Specifications

Dimensions: (L220mm W185mm H140mm)

Weight(kg) 0.85

Colour: Black or Almond

Operating Environment: 0 C to 50 C

Dial: Tone

Link Flash): 600ms

Power: 9V DC Transformer

(Basic telephone service when power failure)